

# ケーブルサイズ一覧表

## 柔軟耐震型ホイストVCT

サイズ	仕上外径mm	質量kg/km	許容電流値A
3c × 2mm <sup>2</sup>	11.4	190	18
4c × 2mm <sup>2</sup>	12.5	236	17
6c × 1.25mm <sup>2</sup>	13.5	260	11
6c × 2mm <sup>2</sup>	15.2	344	15
8c × 1.25mm <sup>2</sup>	16.4	360	10
8c × 2mm <sup>2</sup>	17.6	460	13
10c × 1.25mm <sup>2</sup>	18.9	460	10
10c × 2mm <sup>2</sup>	18.8	530	13
12c × 1.25mm <sup>2</sup>	19.7	500	9
12c × 2mm <sup>2</sup>	21.7	680	12
12c × 3.5mm <sup>2</sup>	26.8	1000	17
16c × 1.25mm <sup>2</sup>	19.6	550	8
16c × 2mm <sup>2</sup>	22.4	765	10
20c × 1.25mm <sup>2</sup>	21.6	670	7
20c × 2mm <sup>2</sup>	24.5	920	9
30c × 1.25mm <sup>2</sup>	25.7	950	6
3c × 3.5mm <sup>2</sup>	12.4	248	25
4c × 3.5mm <sup>2</sup>	13.7	308	23
3c × 5.5mm <sup>2</sup>	14.9	374	34
4c × 5.5mm <sup>2</sup>	16.4	463	31
3c × 8mm <sup>2</sup>	18.8	570	44
4c × 8mm <sup>2</sup>	21.0	770	40
3c × 14mm <sup>2</sup>	23.3	940	63
4c × 14mm <sup>2</sup>	25.9	1150	57
3c × 22mm <sup>2</sup>	28.0	1350	80
3c × 38mm <sup>2</sup>	33.3	2170	118

## TR-2PNCT (ケーブルリール用)

サイズ	仕上外径mm	質量kg/km	許容電流値A
3c × 3.5mm <sup>2</sup>	14.4	325	35
4c × 3.5mm <sup>2</sup>	15.9	405	31
3c × 5.5mm <sup>2</sup>	16.5	460	45
4c × 5.5mm <sup>2</sup>	18.6	560	40
3c × 8mm <sup>2</sup>	18.8	530	55
4c × 8mm <sup>2</sup>	21	765	50
3c × 14mm <sup>2</sup>	21	870	77
4c × 14mm <sup>2</sup>	24.2	1120	68
3c × 22mm <sup>2</sup>	27	1380	100
3c × 38mm <sup>2</sup>	32	2030	135

※許容電流値はケーブル直線状態での数値です。

## TR-2PNCT補強型(リフティングマグネット用)

サイズ	仕上外径mm	質量kg/km	許容電流値A
2c × 5.5mm <sup>2</sup>	18.0	460	51
2c × 8mm <sup>2</sup>	18.2	500	63
2c × 14mm <sup>2</sup>	22.0	765	88
2c × 22mm <sup>2</sup>	26.6	1145	115

※許容電流値はケーブル直線状態での数値です。

## 柔軟耐震型R-VCT(ワイヤー付 押釦操作用)

サイズ	仕上外径mm	質量kg/km	許容電流値A
4c × 1.25mm <sup>2</sup>	11.4	220	13
6c × 1.25mm <sup>2</sup>	14.9	340	11
6c × 2mm <sup>2</sup>	15.8	410	15
8c × 0.75mm <sup>2</sup>	15.8	350	8
8c × 1.25mm <sup>2</sup>	17.4	440	10
8c × 2mm <sup>2</sup>	17.5	480	14
10c × 0.75mm <sup>2</sup>	17.4	440	7
10c × 1.25mm <sup>2</sup>	18.8	495	10
10c × 2mm <sup>2</sup>	19.6	580	13
12c × 0.75mm <sup>2</sup>	18.8	500	7
12c × 1.25mm <sup>2</sup>	19.6	590	9
14c × 1.25mm <sup>2</sup>	22.0	650	8
16c × 0.75mm <sup>2</sup> B	22.1	580	6
16c × 1.25mm <sup>2</sup> A	20.6	700	8
16c × 1.25mm <sup>2</sup> B	24.5	750	8
20c × 1.25mm <sup>2</sup>	22.4	740	7
26c × 1.25mm <sup>2</sup>	25.2	925	6

## 柔軟耐震型複合VCT

サイズ	仕上外径mm	質量kg/km	許容電流値A
3c × 3.5mm <sup>2</sup> + 3c × 2mm <sup>2</sup>	16.5	405	23/14
3c × 3.5mm <sup>2</sup> + 5c × 2mm <sup>2</sup>	18.7	505	22/13
3c × 3.5mm <sup>2</sup> + 8c × 2mm <sup>2</sup>	23.4	730	19/11
3c × 3.5mm <sup>2</sup> + 12c × 2mm <sup>2</sup>	26.8	960	17/10
4c × 3.5mm <sup>2</sup> + 5c × 2mm <sup>2</sup>	19.9	630	21/12
4c × 3.5mm <sup>2</sup> + 8c × 2mm <sup>2</sup>	25.0	815	18/11
3c × 5.5mm <sup>2</sup> + 3c × 2mm <sup>2</sup>	18.5	510	31/12
3c × 5.5mm <sup>2</sup> + 5c × 2mm <sup>2</sup>	20.5	600	30/12
3c × 5.5mm <sup>2</sup> + 8c × 2mm <sup>2</sup>	24.2	820	26/10
3c × 5.5mm <sup>2</sup> + 12c × 2mm <sup>2</sup>	29.2	1120	24/10
4c × 5.5mm <sup>2</sup> + 5c × 2mm <sup>2</sup>	21.8	835	28/11
4c × 5.5mm <sup>2</sup> + 8c × 2mm <sup>2</sup>	26.0	940	25/10
3c × 8mm <sup>2</sup> + 3c × 2mm <sup>2</sup>	20.0	630	40/11
3c × 8mm <sup>2</sup> + 5c × 2mm <sup>2</sup>	22.0	720	39/11
3c × 8mm <sup>2</sup> + 8c × 2mm <sup>2</sup>	26.3	980	35/10
3c × 8mm <sup>2</sup> + 12c × 2mm <sup>2</sup>	31.6	1290	33/9
4c × 8mm <sup>2</sup> + 5c × 2mm <sup>2</sup>	24.5	960	37/10
3c × 14mm <sup>2</sup> + 3c × 2mm <sup>2</sup>	23.5	930	60/10
3c × 14mm <sup>2</sup> + 6c × 2mm <sup>2</sup>	25.8	1080	58/9
3c × 14mm <sup>2</sup> + 8c × 2mm <sup>2</sup>	30.2	1320	52/8
3c × 22mm <sup>2</sup> + 5c × 2mm <sup>2</sup>	28.6	1390	76/8
3c × 22mm <sup>2</sup> + 8c × 2mm <sup>2</sup>	33.4	1680	68/7